

### EARTH BONDING POINT

Earth Bonding Points are used for proving earthing continuity and a multiple bonding point, these bonding points are available with one, two and four hole connections. When cast into concrete they connect the re-bar to the main earthing or lightning protection system. These are also available with variety of tail lengths to suit deferent applications the tail ends are of 70 mm<sup>2</sup> yellow green pvc coated stranded cable which are pre welded by exothermic welding method.

Body - Gunmetal, Bolts - Al Bronze, Phosphor Bronze and SS  
BS EN 50164-1:2000 (8 Nm.)



### BONDING POINT

Product Ref.	No. of Holes	L	W
BP1	1	77	49
BP2	2	71	69
BP4	3	80	63

### BONDING POINT WITH TAIL

Product Ref.	No. of Holes	L	W	T
BP150	1	76	40	500
BP250	2	76	79	500
BP2100		76	79	1000
BP210		76	79	1500
BP2300		76	79	3000
BP450	4	80	64	500
BP4100		80	64	1000
BP4300		80	64	3000

### BONDING POINT WITH TAPE

Product Ref.	No. of Holes	L	W	T
BPT	2	82	54	-
BPT250		82	54	500
BPT2100		82	54	1000
BPT2150		82	54	1500
BPT2300		82	54	3000