



### BRASS CABLE GLAND : A1/A2

A1/A2 BRASS CABLE GLANDS SUITABLE FOR ALL TYPES OF UNARMoured CABLES, PLASTIC/RUBBER SHEATHED. THIS GLAND PROVIDES A SEAL ON THE OUTER SHEATH OF THE CABLE.

RECOMMENDED TO USE PVC SHROUD FOR ADDITIONAL INGRESS PROTECTION.

**TYPE :** A1/A2

**GLAND MATERIAL :** BRASS

**DESIGN SPECIFICATION :** BS 6121: PART 1: 1989

**CABLE TYPE :** UNARMoured

**SEALING AREA :** OUTER SHEATH

Cat #	Gland Size	Cable Dimensions Accommodated		Gland Dimensions				
		Overall Dia		Dia 'A'	Dia 'B'	Metric Entry Thread 'C'	Minimum Thread Length 'D'	Across Flat 'F' Max
		Min	Max					
HGA220S	20S	8.0	11.5	11.9	15.4	20	15	23.6
HGA220L	20L	11.0	13.5	14.5	17.9	20	15	26.9
HGA225S	25S	13.0	16.5	16.5	20.3	25	15	30.5
HGA225L	25L	13.0	19.5	20.7	27.4	25	15	35.5
HGA232S/L	32S/L	19.0	25.5	26.9	31.7	32	15	41.3
HGA240S/L	40S/L	25.0	32.0	32.5	37.1	40	15	47.0
HGA250S	50S	31.5	37.0	38.6	44.2	50	15	55.0
HGA250L	50L	36.5	43.0	44.0	48.9	50	15	60.0
HGA263S	63S	42.5	50.0	50.3	56.1	63	15	64.8
HGA263L	63L	49.5	55.0	56.4	60.2	63	15	69.9
HGA275S	75S	54.5	61.0	62.2	67.2	75	15	78.8
HGA275L	75L	60.5	67.0	68.3	73.1	75	15	84.6
HGA290S/L	90S/L	65.0	78.0	70.5	80.3	90	15	102.6

(All Dimensions in mm)