



## COPPER FLEXIBLE BRAIDS

Material : Electrolytic high conductivity-Copper  
 Finish : Electro Tinned Plated



Product Ref. Crimped with Lugs	Size mm <sup>2</sup>	Current AMP Rating	Dimensions mm		Product Ref. Crimped with Connectors
			J	E	
HGFL4 50-50	4	50	50	6	HGFC4 50-50
HGFL4 50-100		50	100	6	HGFC4 50-100
HGFL4 50-150		50	150	6	HGFC4 50-150
HGFL4 50-200		50	200	6	HGFC4 50-200
HGFL10 90-50	10	90	50	6	HGFC10 90-50
HGFL10 90-100		90	100	6	HGFC10 90-100
HGFL10 90-150		90	150	6	HGFC10 90-150
HGFL10 90-200		90	200	6	HGFC10 90-200
HGFL16 125-100	16	125	100	8.5	HGFC16 125-100
HGFL16 125-150		125	150	8.5	HGFC16 125-150
HGFL16 125-200		125	200	8.5	HGFC16 125-200
HGFL16 125-250		125	250	8.5	HGFC16 125-250
HGFL16 125-300		125	300	8.5	HGFC16 125-300
HGFL25 160-100	25	160	100	10	HGFC25 160-100
HGFL25 160-150		160	150	10	HGFC25 160-150
HGFL25 160-200		160	200	10	HGFC25 160-200
HGFL25 160-250		160	250	10	HGFC25 160-250
HGFL25 160-300		160	300	10	HGFC25 160-300
HGFL30 180-100	30	180	100	10	HGFC30 180-100
HGFL30 180-150		180	150	10	HGFC30 180-150
HGFL30 180-200		180	200	10	HGFC30 180-200
HGFL30 180-250		180	250	10	HGFC30 180-250
HGFL30 180-300		180	300	10	HGFC30 180-300
HGFL35 210-100	35	210	100	10	HGFC35 210-100
HGFL35 210-150		210	150	10	HGFC35 210-150
HGFL35 210-200		210	200	10	HGFC35 210-200
HGFL35 210-250		210	250	10	HGFC35 210-250
HGFL35 210-300		210	300	10	HGFC35 210-300
HGFL50 250-100	50	250	100	12	HGFC50 250-100
HGFL50 250-150		250	150	12	HGFC50 250-150
HGFL50 250-200		250	200	12	HGFC50 250-200
HGFL50 250-250		250	250	12	HGFC50 250-250
HGFL50 250-300		250	300	12	HGFC50 250-300

(All Dimensions in mm)